



CineView Master 4K

Accsoon CineView Master 4K Specification	Transmitter	Receiver
A/V Processor	8K High Performance A/V Processor	
Protocol	Accsoon Proprietary RTMS 4.0 Protocol	
Video Input	HDMI, 3G SDI	
Video Output	HDMI Loop-Out	HDMI, 3G SDI
USB-C Video Output to iOS	√	/
SDI Input Format	1080p: 23.98/24/25/29.97/30/50/59.94/60fps Level A/B 1080i: 50/59.94/60i 720p: 50/59.94/60p	
HDMI Input Format	4K (3840*2160): 23.98/24/25/29.97/30/50/59.94/60p 1080p: 23.98/24/25/29.97/30/50/59.94/60p 1080i: 50/59.94/60i 720p: 50/59.94/60p	
SDI Output Format		1080p: 24/25/30/50/60p Level A 1080i: 50/60i 720p: 50/60p
HDMI Output Format		4K (3840*2160): 24/25/30/50/60p 1080p: 24/25/30/50/60p 1080i: 50/60i 720p: 50/60p
HDMI Loop-out Format	Identical to the HDMI video input	
DC Port	5.5mmx2.1mm, center positive	
DC Voltage	7.4~16.8V	
Battery	Compatible with NP-F550, NP-F750, NP-F970	
Audio	48KHz 16/20/24bit	
Latency	1080p < 25ms 4K < 35ms (Camera latency not included)	
Transmission Range	≥ 2.5 km (No obstacles, no interference)	
Operating Environment Temperature	-10~40°C	
Power Consumption	6.5W average *Without powering other devices	5.0W average
Dimensions (Antennas Not Included)	130mm x 95mm x 32 mm	
Weight (Antennas Not Included)	322g	320g