

# UNIX-0BL

## HEDBOX UNIX-0BL V-LOCK MOUNT PROFESSIONAL CINE BATTERY PLATE WITH 3X D-TAP (14.8V/10A) + 1 X USB (5.1V/2.1A) AND 1X BREAKAWAY 50CM CABLE 2-PIN PUSH PULL FHG.1B.302 MALE RIGHT ANGLE CONNECTOR

---

### OVERVIEW:

Hedbox UNIX-0BL V-Lock Mount Professional Cine Battery Plate with 1 x USB (5.1V/2.1A) + 3x D-Tap (14.8V/10A) and **1x Breakaway 50cm Cable with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector**. UNIX Professional Cine Battery V-Mount Plate enables the use of V-Lock battery packs on cameras and/or numerous professional peripherals simultaneously. Featuring a high-quality aluminium v-lock release, Hedbox UNIX plates are designed and tested for up to 10,000 battery cycles.

Three (3) D-Tap DC Power Outputs provide 14.8V / 10A for extra devices and peripherals such as on-board recorders, LED lights, monitors, remote follow focus, wireless transmitters etc. A built-in USB 5V / 2.1A Power Output is located on the top of the UNIX plate.

Designed with versatility in mind UNIX plates have multiple mounting holes to provide universal camera connection or peripheral mounting – 4x M3x12 screws are included with UNIX to mount the plate as required. The UNIX-0BL includes a hard-wired 50cm power cable **with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector** that can be used to power Teradek products, and various professional photo/video devices that accept FGG.0B.302 or FHG.1B.302 Connectors.

---

### FEATURES:

#### **Supplied Breakaway 50cm DC Cable with with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector**

With an installed breakaway DC 14.8V / 10A / 148W power cable, UNIX-0BL can be used to power Teradek products and various cameras and devices in the video and photo market. The breakaway cable is a 50cm long, with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector included.

#### **High Quality Aluminium V-lock release**

Adopting technology that allowed us to use a high-quality aluminum alloy V-lock release, the lock and unlock provides up to 10,000 cycles for a V-mount battery on the Unix plate.

#### **3 x D-Tap DC Power Output**

Unix provides three D-Tap 14.8V / 10A DC power outputs. Three D-taps allow for extra powering for cameras, on board recorders, LED lights, monitors, remote follow focus, wireless transition systems, etc.

#### **Multiple Mounting holes for universal camera connection**

With multiple mounting holes, (4 x M3x12 screws provided) Unix is able to mount on to any device or camera connection.

#### **Build-in USB 5V / 2.1A Power Out Socket**

The USB 5V / 2.1A output can be used to power any external USB electronic devices. This function allows you to use the Unix V-lock plate like a power station to charge your cell phone, tablet, or any other electronic devices that can be powered with USB 5V / 2.1A power.

---

### INCLUDED IN BOX:

- 1 X **UNIX-0BL** V-MOUNT PLATE WITH BREAKAWAY 50CM CABLE 2-PIN PUSH PULL FHG.1B.302 MALE RIGHT ANGLE CONNECTOR
- 1 X SET SCREW M3X12 (4PCS)
- 1 X USER MANUAL
- 1 X 2 YEAR LIMITED MANUFACTURER'S WARRANTY

**SPECIFICATION:**

<b>Model :</b>	<b>UNIX-0BL V-Mount Adapter Power Plate</b>
<b>Battery Mount :</b>	<b>V-Lock Mount</b>
<b>D-Tap Power Out 1 :</b>	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
<b>D-Tap Power Out 2 :</b>	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
<b>D-Tap Power Out 3 :</b>	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
<b>USB Output :</b>	DC 5V / 2.1A /10W (Max)
<b>Breakaway DC Cable :</b>	<b>DC 14.8V / 10A / 148W (Max) 50cm (length) FHG.1B.302 Male Right Angle Connector included</b>
<b>V-lock release :</b>	High Quality <b>Aluminium Alloy</b>
<b>Operating Temperature :</b>	-20°C to +45°C (-4°F to +113°F)
<b>Dimensions (WxDxH) :</b>	146 x 102 x 26 mm
<b>Weight :</b>	~ 185 g
<b>Mounting :</b>	Multiple mounting holes for universal camera connection